

X790

Structural Steel Pipe Columns

CAFCO® FENDOLITE® M-II, TG & ISOLATEK® Type M-II, TG

Standard Weight Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
3	0.216	0.2	89 x 5.5	38.0	208.0	11/16	1	1-3/8	2-1/16	2-3/4
4	0.237	0.22	102 x 6.0	45.0	175.5	11/16	1	1-3/8	2-1/16	2-3/4
5	0.258	0.25	141 x 6.6	49.4	160.1	11/16	1	1-5/16	2	2-5/8
6	0.28	0.27	168 x 7.1	53.8	147.0	11/16	1	1-5/16	1-15/16	2-9/16
8	0.322	0.31	219 x 8.2	59.0	134.0	5/8	7/8	1-3/16	1-3/4	2-3/8
10	0.365	0.35	273 x 9.3	70.7	111.8	9/16	13/16	1-1/8	1-5/8	2-3/16
12	0.375	0.36	324 x 9.5	73.0	108.3	9/16	13/16	1-1/8	1-5/8	2-3/16

Extra Strong Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
3	0.3	0.27	89 x 7.6	51.3	154.1	11/16	1	1-5/16	1-15/16	2-9/16
4	0.337	0.31	102 x 8.6	62.0	127.5	5/8	7/8	1-3/16	1-3/4	2-3/8
5	0.375	0.35	141 x 9.5	70.2	112.7	9/16	13/16	1-1/8	1-5/8	2-3/16
6	0.432	0.4	168 x 11	81.0	97.6	1/2	3/4	1	1-1/2	2
8	0.5	0.47	219 x 12.7	94.5	83.7	1/2	11/16	15/16	1-3/8	1-13/16
10	0.5	0.48	273 x 12.7	95.6	82.7	1/2	11/16	15/16	1-3/8	1-13/16
12	0.5	0.48	324 x 12.7	96.4	82.0	1/2	11/16	15/16	1-3/8	1-13/16

Double Extra Strong Pipe Columns

Nominal Dia.	Wall Thk	A/P	Metric Desig.	M/D	Hp/A	1-Hour	1-1/2 Hour	2-Hour	3-Hour	4-Hour
3	0.6	0.5	89 x 15.2	95.0	83.2	7/16	11/16	7/8	1-3/8	1-3/4
4	0.674	0.57	102 x 17.1	114.0	69.3	7/16	11/16	7/8	1-3/8	1-3/4
5	0.75	0.65	141 x 19.1	130.3	60.7	7/16	11/16	7/8	1-3/8	1-3/4
6	0.864	0.75	168 x 21.9	150.7	52.5	7/16	11/16	7/8	1-3/8	1-3/4
8	0.875	0.79	219 x 22.2	157.7	50.1	7/16	11/16	7/8	1-3/8	1-3/4

Note: A/P Ratio based on Design Formul.