

PRODUCT DESCRIPTION

CAFCO PRE-COAT / ISOLATEK Type PC is a specially formulated adhesive product for use with the following CAFCO / ISOLATEK Spray-Applied Fire Resistive Materials:

- CAFCO 300 / ISOLATEK Type 300
- CAFCO 300 AC / ISOLATEK Type 300 AC
- CAFCO 300 ES / ISOLATEK Type 300 ES
- CAFCO 300 HS / ISOLATEK Type 300 HS
- CAFCO 300 SB / ISOLATEK Type 300 SB
- CAFCO 304 / ISOLATEK Type 304
- CAFCO 3000 / ISOLATEK Type 3000
- CAFCO 3000 ES / ISOLATEK Type 3000 ES
- CAFCO 400 / ISOLATEK Type 400
- CAFCO 400 AC / ISOLATEK Type 400 AC
- CAFCO 400 ES / ISOLATEK Type 400 ES

CAFCO PRE-COAT / ISOLATEK Type PC is classified by Underwriters Laboratories (UL) for use in specific Designs within the UL Fire Resistance Directory

CAFCO PRE-COAT / ISOLATEK Type PC shall be applied to cover a minimum of 70 percent of corrugated decking, cellular decking, concrete slabs and areas beneath trench headers. The applied thickness of PRE-COAT / ISOLATEK Type PC shall be included in the total thickness required of the CAFCO / ISOLATEK fire protection material.

MAJOR SPECIFICATIONS

CAFCO PRE-COAT / ISOLATEK Type PC is recognized by Underwriters Laboratories (UL) for use as a specially formulated adhesive product.

CAFCO PRE-COAT / ISOLATEK Type PC complies with the requirements of the following specifications when used in conjunction with the referenced SFRMs:

- MasterSpec[®], Section 078100 APPLIED FIREPROOFING (AIA)
- MasterFormat[®] 2014, Section 07 81 00 Applied Fireproofing (CSC,CSI)
- Unified Facilities Guide Specification, UFGS 07 81 00 Spray-Applied Fireproofing (USACE, NAVFAC, AFCEC, NASA)
- Master Construction Specifications, Number 07 81 00 Applied Fireproofing (VA)
- Code of Federal Regulations, Title 40 Protection of the Environment (EPA)
- PBS-P100, Facilities Standards for the Public Buildings Services (GSA)



ISOLATEK INTERNATIONAL is registered with the
AIA Continuing Education System (AIA/CES)



We support our customers with unsurpassed technical expertise and customer service, complemented by an extensive global network of experienced sales representatives and recognized applicators. For detailed product information or for the name of the sales representative in your area please contact us.

The performance data herein reflect our expectations based on tests conducted in accordance with recognized standard methods under controlled conditions. The applicator, general contractor, property owner and/or user MUST read, understand and follow the directions, specifications and/or recommendations set forth in Isolatek International's publications concerning use and application of these products, and should not rely merely on the information contained in this Technical Data Sheet. Isolatek International is not responsible for property damage, bodily injuries, consequential damages, or losses of any kind that arise from or are related to the applicator's general contractor's, or property owner's failure to follow the recommendations set forth in Isolatek International's publications. The sale of these products shall be subject to the Terms and Conditions set forth in the Company's invoices.



Brand

Isolatek International provides passive fireproofing materials under the CAFCO® and FENDOLITE® trademarks throughout the Americas and under the ISOLATEK® trademark throughout the world.

800.631.9600 or 973.347.1200
www.isolatek.com | technical@isolatek.com
technical-international@isolatek.com

ISOLATEK®
Brand