

Section 1 – Chemical Product / Company Information

Product Name: CAFCO® HEAT-SHIELD® ADHESIVE **Effective Date:** July 27, 2015

Product Use/Class: Adhesive for insulation

Supplier: USMPC Buyer Inc, dba Isolatek International
41 Furnace Street
Stanhope NJ 07874
technical@isolatek.com
Toll Free: 1 800 631 9600 **Preparer:** R&D Department

In Case of Emergency Call: CHEMTREC **Supersedes:** August 28, 2013

800.424.9300 (USA) +1 703.527.3887 (Int'l)

Section 2 – Hazards Identification

GHS Classification:	Hazard Category	Route of Exposure
Hazard Class		
Skin Irritation	2	Skin
Skin Sensitizer	1	Skin
Eye Irritation	2B	Eye
Inhalation Toxicity	4	Nose/Mouth

Global Harmonization Labeling and Classification:

Signal word: Warning

Hazard Symbol(s): GHS07



Overview: A thick liquid that poses little immediate hazard.

Primary Route(s) of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

Medical Conditions Prone to Aggravation by Exposure: Sensitive skin; respiratory conditions

Hazard Statements:

H303	May be harmful if swallowed.
H313	May be harmful in contact with skin.
H320	Causes eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements:

P202	Do not handle until safety precautions have been read and understood.
P261	Avoid breathing dust/ fumes/ gas/ mist/ vapours/ spray.

CAFCO® HEAT-SHIELD® Adhesive

Safety Data Sheet

P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284	In case of inadequate ventilation, wear respiratory protection.
P403	Store in a well ventilated place.
EUH401	To avoid risks to human health and the environment, comply with the instructions for use.

Response:

P301+P330 P331+P312	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/ physician if you feel unwell.
P302+P352+ P332+P313+ P363	IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.
P304+P340+ P342+P313	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Get medical advice/ attention.
P305+P351+ P338+P337+ P313	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.

Storage:

P402+P403+ P404+P410+ P411	Store in a dry place. Store in a well ventilated place. Store in a closed container. Protect from sunlight. Store at temperatures not exceeding 38°C/ 100°F.
---	--

Disposal:

P501	Dispose of contents/container in accordance with local/regional/national/international regulations (see section 13).
-------------	--

Section 3 – Composition / Information On Ingredients

Chemical Name	CAS Number	Wt. %
Vinyl acrylic copolymer emulsion	mixture	<60
Vinyl acetate	108-05-4	<0.1
Acetaldehyde	75-07-0	<0.1

Section 4 – First Aid Measures

General – If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

First Aid – Skin Contact: Wash with soap and water. Remove contaminated clothing. If persistent irritation occurs, seek medical attention.

First Aid – Eye Contact: Flush eyes thoroughly with copious amounts of water. Seek medical attention if irritation persists.

First Aid – Inhalation: Remove to fresh air. Seek medical attention if irritation persists.

First Aid – Ingestion: If swallowed do not induce vomiting. Rinse mouth out with water. If Irritation persists seek medical attention.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

Ingestion may cause gastrointestinal irritation, nausea, vomiting, and diarrhea.
Repeated or prolonged exposure may cause irritation of eyes and skin.

ISOLATEK® HEAT-SHIELD® Adhesive

Safety Data Sheet

Section 5 – Fire Fighting Measures

Extinguishing Media: ABC dry chemical, foam or carbon dioxide.

Unusual Fire & Explosion Hazards: The pressure in sealed containers can increase under the influence of heat and rupture.

Special Firefighting Procedures: Wear positive pressure self-contained NIOSH approved breathing equipment and approved protective equipment if necessary. Prevent fire extinguishing water from contaminating surface water or the ground water system.

Section 6 – Accidental Release Measures

Personal precautions, Protective Equipment, and Emergency Response: Use personal protective equipment as recommended in section 8.

Environmental precautions: The product should not be allowed to enter drains or soil.

Methods and materials for containment and cleaning up: Large spills can be controlled mechanically by pumping for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, sawdust). Clean contaminated floors thoroughly while observing environmental regulations.

Section 7 – Handling And Storage

Precautions for safe handling: When working with any chemical product, use good workplace procedures. Do not cut, puncture, or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well ventilated conditions. Avoid skin and eye contact. Avoid inhalation of mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse.

Conditions for safe storage: Store between 4 and 38°C (40 and 100°F). Keep away from heat, sparks, and open flames. Avoid extreme heat or cold. Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Empty container contains residual product which may exhibit hazards of product. Do not reuse empty container.

Section 8 – Exposure Controls / Personal Protection

Permissible Exposure Limits

Chemical Name	CAS Number	OSHA PEL	ACGIH TLV	NIOSH	Mexico
Vinyl acrylic copolymer emulsion	mixture	N/E	N/E	N/E	N/E
Vinyl acetate	108-05-4	N/E	15 ppm	15 mg/m3	N/E
Acetaldehyde	75-07-0	200 ppm TWA	25 ppm C	N/E	N/E

Engineering Controls: Provide ventilation to ensure compliance with applicable exposure limits.

Respiratory Protection: In case of vapor formation use a respirator with an approved filter.

Skin Protection: Wear rubber, nitrile, or latex gloves. Use typical long sleeve work clothing or a "Tyvek" type suit .

Eye Protection: Wear proper eye protection; at minimum, safety glasses with side shields.

Work / Hygienic Practices: Use proper personal protective equipment. Eye wash stations are recommended in the work area. Do not flush product into drains. Follow standard industry hygienic rules, such as but not limited to, not smoking or drinking while using product and washing hands at the end of the day.

Section 9 – Physical And Chemical Properties

Appearance: Liquid, Aqueous dispersion
Odor: Slight
pH: 4-6

ISOLATEK® HEAT-SHIELD® Adhesive

Safety Data Sheet

Melting Point (°F):	32F
Boiling Point (°F):	>212F
Flash Point:	>200F
Evaporation Rate:	Not Applicable
Flammability:	Not flammable
Lower Explosive Limit:	N/E
Upper Explosive Limit:	N/E
Vapor Pressure (mm Hg):	N/E
Relative Density (kg/mm3)	0.9-1.1
Solubility in Water:	Insoluble but dispersible
Specific Gravity (H₂O=1):	1.06
Physical State:	Liquid
% Volatiles:	50
Viscosity	N/E
Auto ignition temperature	N/E

Section 10 – Stability And Reactivity

Chemical Stability (under normal conditions):	Stable
Possibility of Hazardous Reactions:	None
Conditions to Avoid:	Avoid extreme temperatures and direct sunlight.
Incompatibility:	None known.
Hazardous Decomposition Products:	No hazardous decomposition products are known.
Hazardous Polymerization:	No hazardous polymerization will occur under normal conditions.

Section 11 – Toxicological Information

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of personal protective equipment and handling procedures to minimize exposure.

Eyes: May cause eye irritation.

Skin: Causes skin irritation.

Inhalation: High airborne concentrations of vapor resulting may cause irritation of the respiratory tract and mucous membranes.

Ingestion: Not likely route of exposure but ingestion may cause irritation.

Carcinogenicity	IARC			NTP		OSHA
	Group 1	Group 2A	Group 2B	Known	Suspect	
Chemical Name						
Vinyl acrylic copolymer emulsion	No	No	No	No	No	No

Acute toxicity

No toxicity studies have been conducted on this product.

Chronic effects – For this category no toxicological test data is available for the whole product.

Carcinogenicity - For this category no toxicological test data is available for the whole product.

Mutagenicity - For this category no toxicological test data is available for the whole product.

Teratogenicity - For this category no toxicological test data is available for the whole product.

Developmental effects - For this category no toxicological test data is available for the whole product.

Fertility effects - For this category no toxicological test data is available for the whole product.

Target organs – For this category no toxicological test data is available for the whole product.

Review Section 2 for any additional assessments

Section 12 – Ecological Information

Ecological Information: No ecological testing has been conducted on this product. It is expected to be practically non-toxic to aquatic organisms on an acute basis.

Persistence and degradability: The product is estimated to be readily biodegradable according to OECD classification.

Bioaccumulative potential: Not likely

Mobility in soil: N/E

ISOLATEK® HEAT-SHIELD® Adhesive

Safety Data Sheet

Section 13 – Disposal Considerations

Disposal Information: Do not allow the product to enter drains, water courses or the soil. Liquids cannot be disposed of in a landfill. Allow liquid material to dry. Dispose of in accordance with federal, state and local regulations.

Section 14 – Transportation Information

Proper Shipping Name: Not regulated – See Bill of Lading for details
Technical Name: Not regulated
Hazard Class: Not regulated
UN/NA Number: Not regulated
Additional Notes: None

Section 15 – Regulatory Information

US Regulations

HCS Classification Irritating material

SARA 313 - Supplier Notification None

U.S. Federal Regulations SARA 311/312	Immediate Health (Acute)	Delayed Health (Chronic)	FIRE	PRESSURE	REACTIVE
	No	No	No	No	No

INTERNATIONAL REGULATIONS AS FOLLOWS:

Chemical Inventory Status

All chemicals in this product are listed or exempt from listing in the following:

U.S	Canada	Europe	Australia	Korea
TSCA	DSL NDSL	EINECS ELINCS	AICS	ECL
Yes	Yes No	Yes	Yes	Yes

CANADIAN WHMIS

This SDS has been prepared in compliance with Controlled Product Regulations and contains all information required.

CANADIAN WHMIS CLASS: D2B

HMIS Ratings

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION	B


ISOLATEK® HEAT-SHIELD® Adhesive

Safety Data Sheet

Section 16 – Other Information

N/E – Non Established
N/A – Not Applicable

NFPA:



Prepared By: Research Department, U.S.A.
Telephone: (973) 347-1200

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. **VENDOR SPECIFICALLY DISCLAIMS ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** In no event shall the vendor be liable for special, indirect or consequential damages.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes all risks in his use of the material.